



**ДЕКЛАРАЦИЯ ЗА СЪОТВЕТСТВИЕ**  
**Decking EC**  
**ФК 8.2.4-8.2**

„ТРАНСПЛАСТ МПД“ ЕООД

Ревизия: 0  
Версия: 0  
Дата: 04.06.2012 г.  
Лист 2 / Вс. Листа 2

# „TRANSPLAST MPD“ LTD

## DECLARATION OF CONFORMITY

SUPPLIER	„TRANSPLAST MPD“ LTD.
ADDRESS	Bulgaria, Plovdiv 4004, Komatevo, Ring Road Nr.15 A
PRODUCT	WOODPLASTIC COMPOSITE (WPC)
WEBSITE	<a href="http://darvolex.com">http://darvolex.com</a>
E-mail	<a href="mailto:info@darvolex.com">info@darvolex.com</a>

„TRANSPLAST MPD“ LTD declares that:

### The product **DARVOLEX – D**

Fulfills the requirements of the following Directives according to the Regulation for the Fundamental requirements for building constructions and evaluating of the construction materials (carried by Council of Ministry's decree Nr. 325 from 6<sup>th</sup> of December 2006; Publ., Official Journal , copy 106 from 2006; Emendation, OJ copy 3 and copy 9 from 2007; Correction, OJ Copy 82 from 2008, OJ copy 5 from 2010, OJ copy 7 from 2011 and OJ copy 18 from 2012)

**EU Directive 89/106/EEC, and modification**  
**Directive 93/68/EEC of Construction Products**

And further Conform with the following EU  
Harmonized Standards:

**EN 13986:2004**

**EN 14342:2005+A1:2008**

Purpose of the product:  
**Framework elements for inner  
and outdoor constructions**  
/restaurant decorations, inn  
decorations and restoration of  
ancient buildings/

Issued:  
Plovdiv  
04<sup>th</sup> of June 2012

NAME: DIMITAR DEVEDZHIEV  
OCCUPATION: MANAGER  
SIGNATURE:



<b>CE</b>	
TRANSPLAST MPD LTD., Plovdiv 4004, Komatevo, Ring Road Nr. 15A	
12	
EN 14342:2005+A1:2008	
EN 13986:2004	
Wood Plastic Composite DARVOLEX - D	
Height of the profile:	26mm
Thickness swelling per 24 hours:	0.27%
Flexural modulus:	6314.94 MPa
Flexural strength:	39.41 MPa
Slippery:	USRV 35
Burning behavior:	Efl
Formaldehyde release:	E1
Pentachlorophenol release:	< 1ppm